

HOT SPOT® COLLECTION

PACE™



5

Seats

24

Jets

300

Gallons

Double
Lounge

Style

6'10" x 6'10" x 33"

Dimensions

115v/20 amp**

Voltage

HOT SPOT® COLLECTION

PACE™



Pace spa shown with Alpine White shell, Havana Cabinet and Havana Everwood step.

Spa Shell



Alpine White



Pearl



Pebble



Tuscan Sun

Cabinet



Almond



Havana



Storm

Spa Cover



Nutmeg



Stone

Seating Capacity

5 adults

Dimensions

6'10" x 6'10" x 33" / 2.08m x 2.08m x 0.84m

Water Capacity

300 gallons/1,135 liters

Weight

775 lbs./350 kg dry; 4,150 lbs./1,880 kg filled*

Spa Shell Options

Alpine White, Pearl, Pebble or Tuscan Sun

Cabinet Options

Almond, Havana, or Storm

Jets - 24

(all with stainless steel trim)

3 XL Directional Hydromassage jets
2 Directional Hydromassage jets
2 Rotary Hydromassage jets
17 Directional Precision® jets

Jet Pump

Wavemaster® 6200; Two-speed,
1.5 HP Continuous Duty,
3.2 HP Breakdown Torque

Water Care System

FROG® In-Line Cartridge Ready

Ozone System (Optional)

FreshWater® III Corona Discharge

Control System

IQ 2020® 115v/20 amp**
(Includes G.F.C.I. protected power cord)
or 115v/30amp*** or 230v/50amp***, 60Hz

Lighting (interior)

10 multi-color LED points of light, dimmable

Lighting (exterior)

4 multi-color LED points of light, dimmable

Heater

No-Fault® 1000w/115v, or 4000w230v

Energy Efficiency

FiberCor® Insulation; Certified to the
APSP 14 National Standard and the California
Energy Commission (CEC) in accordance
with California law

Effective Filtration Area

30 sq. ft., top loading

Vinyl Cover

3.5" to 2.5" tapered, 2 lb. density foam core
Nutmeg or Storm

Cover Lifter (Optional)

CoverCradle®, CoverCradle II, or UpRite®

Steps (Optional)

Everwood® Step - Almond, Havana, or Storm
Polymer Step - Ash

Entertainment System

Wireless Sound System

Actual colors and products may vary from print representation. See dealer to verify. * Includes water and 5 adults weighing 175 lbs. each. **Requires a dedicated circuit supplied to the unit at all times. Electrical requirements will vary outside the U.S.

*** G.F.C.I. protected sub-panel required in 30amp conversion or 220v mode. Export models available in 230v, 50Hz, 1000w heater.